

PRODUCT: TRIPLE CUT COMPOUND

PART NUMBER: 100019 **Quart** **12 units/case**

DESCRIPTION: Triple Cut compound is a multi-phase compound for use in removing 1200 grit and finer sand scratches. It is the most effective compound on the market on today's technologically advanced clears. Triple Cut compound is a versatile product in any paint finishing system and is easy to clean up. Contains no silicones or waxes.

USES: Removal and leveling of topcoat imperfections found after painting, such as:

Orange Peel	Dirt Nibs
Paint Runs	Sand Marks
Paint Sags	Oxidation

APPROVED FINISHES:

- Lacquer Topcoats
- Acrylic Enamel Topcoats
- Basecoat /Clearcoat Systems
- Acrylic Urethane Topcoats

All paint coatings are different in their drying and curing characteristics based on their chemistry, drying mechanism, (air dry vs. bake), and environmental conditions. It is important that proper sanding and buffing times (based on the type of coating) are followed according to the paint manufacturer's recommendations.

PREPARATION: Identify severity of topcoat imperfection and choose sand paper grit accordingly (i.e. heavy orange peel 1,200 grit). After sanding wipe area to remove sanding residue. Clean buffing pad occasionally before and during use with a cleaning spur tool.

APPLICATION: Shake product well before using. Apply product sparingly, enough to work a two foot square area, onto the sanded area. Spread product with buffing pad and begin buffing with light to moderate pressure at approximately 1400 rpm. Continue buffing until sand marks are removed.

Inspect repair area for sand marks. In some cases all marks are not removed due to buffing techniques, therefore a second application maybe necessary.

Note: If product begins to dry or additional buffing is needed, mist water onto the finish to reactivate the product.

FINISH: Wipe down surface with a soft, clean, dry cloth to remove residue and dust. On dark colors, follow Triple Cut with #032 Triple Gloss for an exceptional finish.

TECHNICAL SPECIFICATIONS:

- | | |
|------------------------|---|
| • Appearance | Blue Paste |
| • VOC | Refer to Section 9 of the Safety Data Sheet |
| • Residue clean-up | Excellent |
| • Water Soluble | Yes |
| • Maximum sanding grit | 1,200 grit wet, 1,500 grit dry DA |
| • Scent | Cherry |

SAFETY & HANDLING:

Read all directions and warnings prior to using Evercoat products. Safety Data Sheets can be found online at www.evercoat.com.

CAUTION: Keep product from freezing.